

KDP-S45

Plastic Dome Camera

SONY/SHARP CCD

Lens: 3.6mm Board lens/F2.0

Dimension : Ø 118 x 74(H) mm

Weight:250g



Model	KDP-1030S45	KDP-639S45	KDP-409S45	KDP-405S45	KDP-2421S45
Image Sensor	1/4"CMOS	1/3"SONY	1/3"SONY	1/3"SONY	1/3"SHARP
TV System	PAL/NTSC				
Horizontal Resolution	480 TV Line	540 TV Line Low Illumination	540 TV Line	420 TV Line	420 TV Line
Pixels	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:795(H)×596(V) NTSC:811(H)×508(V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:500(H)×582(V) NTSC:510(H)×492(V)
IR LED					
IR Series Distance					
Lens	3.6mm Board lens/F2.0				
Sync System	Internal				
IR Status	Under 10 Lux By CDS				
IR Power On	CDS Auto Control				
Usable Illumination	0 Lux/F2.0 (LED ON)				
S/N Ratio	≥ 48dB (AGC OFF)				
Gamma Correction	0.45				
Video Out	Composite Signal (1.0Vp-p, 75Ω)				
Scanning System	PAL:625 Lines, 50 Field/Sec;NTSC:525 Lines, 60 Field/Sec				
Electronic Shutter Time	Auto:PAL 1/50-1/100,000Sec;NTSC 1/60-1/100,000Sec				
Operation Temperature	-10℃ ~ +50℃ RH95% Max				
Storage Temperature	-20℃ ~ +60℃ RH95% Max				
White Balance	Auto				
Power Source	DC12V 150mA				
Dimension	ø 118 x 74(H) mm				
Weight	250g				